

LG VIZUON™ LD284TG

Gloss white, 3 year monomeric vinyl with clear 'air-free' repositionable and removable adhesive

Product description

For printing with Solvent, Latex and UV inks.

Gloss white, 100µ calendered monomeric PVC. Supplied with a clear 'air-free' repositionable and removable solvent acrylic adhesive on a heat stable structured 130gsm double sided PE coated release liner.

Typical uses

Short term internal and external general-purpose advertising and promotion, especially suited to window graphic applications. Can be applied dry, the air free adhesive makes application easy, as any trapped air can be pushed out from under the vinyl using the air free channels.

The product is recommended for simple 2D contours or flat sided applications.

Shelf life

2 year when stored at 15°C to 25°C and 50% RH.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

| | |
|----------------------------|---|
| Film thickness: | 100 microns |
| Adhesive data: | Peel adhesion on glass 24 hrs: 8 – 10 N/25mm |
| Gloss: | >85 (measured at 60° angle) |
| Temperature ranges: | |
| Min. Application: | plus 10°C |
| Service Range: | minus 45° to plus 80°C |
| Flammability: | BS-EN 13501 – 1 |

Application Data

The structured adhesive allows for initial repositioning to ensure the graphic is in the right place. The product is ideal for dry application, avoiding use of application fluids in sensitive environments. The use of high pressure washers is not recommended, especially on intricate cut graphics. Hand washing with soapy water is preferred to avoid damage to the product. Media must be allowed to cure for at least 24 hours prior to initial cleaning. When printed with Solvent inks, sufficient time must be left after printing to allow the out gassing of the solvents in the inks. Prints must ideally be left flat and uncovered for at least 24 hours to allow this process to happen, especially in colder workshops. The use of a hot air blower will greatly improve this process. Product can be laminated with one of our DigiGuard range of laminates or the range of matched clear laminate from LG LD2812G gloss, LD2842G gloss and LD2712M matt.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.

We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | **North Sales:** T 01709 829800
Free Fax 0800 374635 | **E** sales@allprint.co.uk | **W** allprint.co.uk



All Print Supplies