Product Data Sheet March 2024

# DigiGUARD FV8-85 Floortex

## B1 fire rated, R11 slip rated textured floor graphic protection PVC film

### **Product description**

200µ textured matt clear PVC laminating/protection film. With a permanent clear, acrylic adhesive and a one side siliconised white release liner.

\_\_\_\_\_

### Typical uses

Suitable for up to 6 months indoor use only. Product has a slip rating of DIN51130 R11. For the protection of floor graphics from wear and tear. Can be used over UV, Eco solvent, Solvent and Latex prints. Product features a good degree of UV block and the adhesive has excellent resistance to humidity and ageing.

-----

#### Shelf life

2 years when stored in original packaging at 21°C and 50% RH.

-----

### Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

**Film thickness:** 200 microns including adhesive

Liner weight: 65gsm

UV block (UVa): Min 85%

**Temperature ranges:** Application Range: plus 2°C to plus 30°C

Service Range: minus 40° to plus 80°C

**Peel Values:** 24hr/180° - 11 N/25mm (Direct to S/S)

Slip Resistance: Rated to DIN 51 130 and BGR 181 Anti slip Group R11.

**Fire rating**: DIN 4102 B1 rated.

#### **Application Data**

To ensure good bond strength, product must be applied to dry, clean, grease free surfaces.

Once laminated, it is recommended to leave the job for at least 4 hours to allow the adhesive to cure before trimming or rolling. For best results the film should be applied dry, using a laminator without heat.

Because of the variety of possible uses, the purchaser should carefully consider the fitness and performance of the product for their intended use.

6 months indoor use, however due to the nature of the PVC surface; users must check the suitability depending on the amount of foot traffic over the graphic.

Areas of use: Customer Areas in Financial Institutions, Stairs in Schools, General Indoor Entrance Halls Pharmacies, Hairdressing Salons, Doctors Surgeries, Hospital (Flooring Area), Customer Areas in Stores and Supermarkets, Restaurants (Service Areas), Underground and Multi-Storey Car Parks, Serving Areas for Unwrapped goods and Bakery Items, Self Service Restaurants (Food preparing area), Sanitary Areas (Toilets).

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use. We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | North Sales: T 01709 829800 Free Fax 0800 374635 | E sales@allprint.co.uk | W allprint.co.uk

