

Self-wound clear mount film

Product description

Product features a double-sided permanent adhesive with a clear 12µ polyester carrier film on a double-side special coated release liner.

Typical uses

Suitable for internal and external use. Works well with a wide variety of substrates, including MDF and foam PVC boards.

Shelf life

2 years when stored in original packaging at 10°C - 30°C and 30% - 65% RH.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

PET carrier film thickness: 12 microns

Adhesive thickness:	60 micron total
Temperature ranges:	Application Range: >10°C Service Range: minus 40°C to plus 70°C
Peel Values:	24hr - 11 N/25mm (Direct to aluminium)

Application Data

Product is best applied to graphics using a laminator to ensure a consistent even clear bond.

Product must be applied to dry, clean, dust and grease free surfaces.

If the product is being applied to the back of ink jet prints, it is essential to leave the print to thoroughly dry before applying the mount film. As a wide variety of substrates can be mounted, it is recommended that a test is carried out to determine the print is dry enough for lamination. As a general rule, a minimum of 4 hours is recommended at normal room conditions of 23°C and 50%RH. At lower application temperatures this time may need to be extended.

The product is not clear enough to use for window applications. We recommend our FM2 Optically Clear Mount for this.

It is recommended for flat surfaces only and is not suitable for heavy contours or 3D curves.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use. We reserve the right to make changes to specifications without prior notice.



All Print Supplies

March 2024