

DigiPRINT DisplayFAB

Matt white polyester fabric with silver light stop for roll-ups

Product description

A 280µ textured tear resistant matt white non-PVC fabric for roll ups. For Solvent, Latex and UV inks.

Typical uses

Product is suitable for internal and external applications, formulated solely for the quick, easy and economical production of roll up and pull up displays.

Product has a fine woven surface non reflective finish, hangs very flat, with excellent tear resistance, good scratch and scuff resistance. Designed for use un laminated.

Blocks out more than 95% of the light, so ideal for use in strongly lit areas.

Shelf life

2 years unprinted when stored at 10°C - 30°C and 30% - 65% RH.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

Media thickness: 280 ±10 microns

Weight: 260 ±10 gsm

Opacity: >95%

L* a* b*: 91.45, -0.92, -0.45 (typical value)

Gloss Level (60°): <10

Fire rating: A fire rating is not possible with this product.

Application Data

It is essential to ensure prints are dry before post print handling.

Ensure the use of a fresh sharp blade when manually trimming to give a clean cut to the fabric base.

Contact our sales team for profiles and media settings to help you get the best out of this media.

Due to woven nature of the surface, product is not suitable for lamination.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.
We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | North Sales: T 01709 829800
Free Fax 0800 374635 | E sales@allprint.co.uk | W allprint.co.uk



All Print Supplies