

DS-C-2065F

High tack clear 0.2mm thick film double-sided tape

Product description

A transparent, double-sided self-adhesive tape consisting of a PET film carrier and a high tack, high shear plasticiser resistant solvent acrylic adhesive.

Our Tesa 4965 alternative.

Typical uses

Suitable for both indoor and outdoor use.

Product can be used for fixing both smooth and rough surfaces.

Due to the high mass of adhesive it has excellent adhesion to metals and also good performance even to low energy surface such as PP and PE.

Product features good resistance to aging and humidity.

Shelf life

2 years when stored in original packaging at 21°C and 50% RH.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated.

Adhesive and carrier thickness: 210 microns

Carrier thickness: 12 microns

Temperature ranges:

Application temperature: > plus 15°C

Service range: minus 30° to plus 160°C

Peel Values: 20min/180° - 30 N/25mm
24hr/180° - 40 N/25mm
(Direct to stainless steel)

Shear strength (AFERA 5012): 500 hours

Chem resistance: Resistant to most oils, grease, fuels, aliphatic solvents, weak acids, salts and alkalis.

Application Data

Product is designed for use on a wide range of surfaces, however we recommend you test an area first to ensure compatibility.

All surfaces need to be clean, dry and free of any grease or liquids to ensure good bonding.

It is essential to ensure good intimate bonding of the surfaces to maximise the strength.

Where possible a squeegee should be used to make sure a good uniform bond is achieved.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.

We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | **North Sales:** T 01709 829800

Free Fax 0800 374635 | **E** sales@allprint.co.uk | **W** allprint.co.uk



All Print Supplies