

DigiPRINT **DS3005****3 year 150µ scuff resistant textured white monomeric film
with permanent grey opaque adhesive****Product description**

For printing with Solvent, Latex and UV inks. 150µ white textured, stable calendered monomeric PVC. Supplied with a grey coloured extra-strong permanent solvent acrylic adhesive on a heat stable 140gsm double-side PE coated release liner.

Typical uses

For short and mid-term internal and external advertising and promotions, where scuff resistance and low levels of reflectivity are needed.

The product is recommended for simple contours or flat-sided applications such as boards or general signage. Perfect for 'print and cut' labels. Bonds well to low surface energy substrates.

Shelf life

2 years when stored in original packaging at 15°C - 25°C and 50% RH.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

Film thickness: 150 microns

Adhesive Data:

180° Peel Adhesion	Stainless Steel	Glass	Polypropylene	MDF
20 min	11	11	9	3
24 hour	12	12	10	4
1 week	12	13	10	5

Dimensional stability: 0.28mm

Temperature ranges:

Min Application: plus 10°C

Service Range: minus 20° to plus 70°C

Flammability: Sample mounted onto aluminium: self-extinguishing. Certificate pending.

Application Data

Allow product to acclimatise to print room conditions before use.

The use of high pressure washers is not recommended, especially on intricate cut graphics.

Hand washing with soapy water is preferred to avoid damage to the product.

When printed with Solvent inks, sufficient time must be left after printing to allow the out gassing of the Solvents in the inks.

Prints must ideally be left flat and uncovered for at least 24 hours to allow this process to happen, especially in colder workshops.

The use of a hot air blower will greatly improve this process.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use. We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | **North Sales:** T 01709 829800

Free Fax 0800 374635 | **E** sales@allprint.co.uk | **W** allprint.co.uk



All Print Supplies