

DigiPRINT **DS3045**

3 year, 100µ single sided blackout gloss white monomeric PVC

Product description

For printing with Solvent, Latex and UV inks.

White gloss, stable calendered monomeric PVC. Supplied with a black permanent solvent acrylic adhesive on a heat stable 120gsm double-side PE coated release liner.

Typical uses

An economical blackout vinyl for short and mid-term internal and external advertising and promotion.

100µ film is easier to handle and fit. The product is recommended for simple contours or flat-sided applications such as boards or general signage. Ideal for permanent over posting of existing graphics.

The vinyl has very high levels of opacity, with almost total light blackout, but not a lightstop

Shelf life

2 years when stored at 15°C to 25°C and 50% RH.

Physical properties (Average Values). Tests made at 23°C and 50%RH unless otherwise stated

Film thickness: 100 microns

Adhesive data:

180° Peel Adhesion	Glass
20 min	13
24 hour	14
1 week	15

Dimensional stability: 0.35mm

Temperature ranges:

Min Application: plus 10°C

Service Range: minus 20° to plus 70°C

Application Data

Suitable for use on a wide range of solvent, UV and latex printers.

Please contact our sales office for available profiles and best setting conditions for this media.

When printed with solvent inks, sufficient time must be left after printing to allow the out gassing of the solvents in the inks. Prints must ideally be left flat and uncovered or stood on end loosely wound for at least 24 hours to allow this process to happen, especially in colder workshops.

The use of a hot air blower will greatly improve this process.

This product can be used un laminated, depending on the application.

We recommend one of our DigiGUARD range of laminates, if a different finish or improved protection is required.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.

We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | North Sales: T 01709 829800

Free Fax 0800 374635 | E sales@allprint.co.uk | W allprint.co.uk



All Print Supplies