

DigiPRINT EF500

Smooth matt scrim PVC banner for Eco-Solvent, Latex and UV Printers

Product description

A matt white scrim reinforced laminated 500gsm PVC banner designed for use on the current range of Eco-Solvent, Latex and UV printers.

Product is designed for single sided prints.

Rolls are supplied with print side wound face out.

Typical uses

A medium weight product and medium strength cost effective banner - suitable for internal banner applications and sign applications and also low stress external applications.

The surface provides good print quality due its smooth surface.

Due to its tear strength product is not recommended for use in high stress 'across the street' type advertising.

Shelf life

1 year when stored at 10°C to 30°C and 30-65% RH, in original packaging.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

Total weight: 500gsm

Thickness: 360 microns

Tensile strength: TD: 320 N/25mm
MD: 370 N/25mm

Tear strength: TD: 105 N
MD: 194 N

Outdoor durability: Up to 1 year in mid European climate
(unprinted media)

Operation range: Minus 20°C to plus 70°C

Application Data

It is essential to ensure the print is dry before post print processing. Prints should be left flat or stood on end and rolled loosely. Not rolled or folded for at least 24 hours to ensure print is dry.

The use of a forced air heater can greatly speed up the drying process.

Standard PVC banner profiles can be used; however, custom made profiles are available for most leading printers. With standard profiles, users must ensure the media is fully dry before handling.

Please contact our sales office for more information.

Product can be stitched, taped, heat welded and grommited. However, care should be taken to avoid damage to printed graphics. The use of our **banner tape BT2** is recommended for banner finishing.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.

We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | **North Sales:** T 01709 829800

Free Fax 0800 374635 | **E** sales@allprint.co.uk | **W** allprint.co.uk



All Print Supplies