

# FM-W-10P

## High tack white 1mm thick PE foam double-sided tape

### Product description

A strong, white 1mm thick PE foam tape coated on both sides with a permanent high tack acrylic adhesive.

---

### Typical uses

Suitable for both indoor and outdoor use. Product can be used for bonding or mounting on irregular surfaces. Product has good temperature resistance, but poor UV stability.

---

### Shelf life

1 year when stored in original packaging at 21°C and 50% RH.

---

### Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated.

**Carrier thickness:** 1mm

**Liner:** 90gsm, silicone coated

#### Temperature ranges:

Application temperature: > plus 10°C

Service range: minus 20° to plus 80°C

**Peel Values:** 24hr/180° - 20 N/25mm  
(note adhesion to substrate is higher than internal strength of foam)  
(Direct to glass)

---

### Application Data

Product is designed for use on a wide range of surfaces, however we recommend you test an area first to ensure compatibility.

All surfaces need to be clean, dry and free of any grease or liquids to ensure good bonding.

It is essential to ensure good intimate bonding of the surfaces to maximise the strength.

Where possible a squeegee should be used to make sure a good uniform bond is achieved.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.

We reserve the right to make changes to specifications without prior notice.

---

South Sales: T 01753 696977 | North Sales: T 01709 829800

Free Fax 0800 374635 | E [sales@allprint.co.uk](mailto:sales@allprint.co.uk) | W [allprint.co.uk](http://allprint.co.uk)



All Print Supplies