Product Data Sheet July 2018

Kleentear 50

Medium tack application tape

Product description

Paper - A standard weight latex saturated paper designed specifically for pre-mask, pre-space and application tape requirements.

Adhesive - A natural latex adhesive with medium tack levels, which achieves consistent transfer of mid-sized cut vinyl graphics. The adhesive system is clean tearing and does not suffer from 'stringing'.

Typical uses

Application tape for medium sized graphics.

Pre-mask for printed vinyl graphics.

All purpose transfer and pre-space tape.

Protection tape for digitally printed graphics.

Shelf life

6 months when stored at 15°C to 25°C and 50% RH.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

Film thickness: 100-113 microns

Adhesive data: Peel adhesion on stainless steel

(PSTC-1) 1 min: 13-15 N/100mm

Tensile strength: 74 N/25mm

Elongation: 3-4%

Tear resistance: 50g

Application Data

Rolls should be stored on end in original packaging away from strong heat and light.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use. We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | North Sales: T 01709 829800 Free Fax 0800 374635 | E sales@allprint.co.uk | W allprint.co.uk

