

OC100

Opal Crystal etch glass effect film

Product description

A 100µ monomeric heavily flaked calendered PVC film used to imitate a sandblasted finish with real sparkle at various viewing angles.

It has a clear, permanent solvent acrylic adhesive and a yellow tinted PE coated release liner for easy weeding.

Typical uses

Suitable for both indoor and outdoor use for up to 3 years.

For the creation of eye catching window graphics or providing privacy in glassed areas.

Product has very good stability, light transmission and levels of privacy and a good UV block.

Shelf life

2 years when stored in original packaging at 21°C and 50% RH.

Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

Film thickness: 100 microns

Liner: 80gsm yellow tinted

UV block (UVa): 35%

Temperature ranges:

Application Range: above plus 10°C

Service Range: minus 40°C to plus 90°C

Peel Values: 20min/180° - 10 N/25mm
24hr/180° - 16 N/25mm
(Direct to glass)

Application Data

Product can be cut on a wide range of vinyl cutters, however it is important to check blade settings to ensure a clean cut. Due to the flakes on the film, an old or blunt blade may need to be changed to ensure a good cut.

Product can be used indoor and outdoor. Designed for use on flat surfaces.

Product should be applied wet, especially with large areas.

Product must be squeegeed well, to remove moisture.

We recommend the use of our **range of application fluids** for preparing the windows.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.

We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | **North Sales:** T 01709 829800

Free Fax 0800 374635 | **E** sales@allprint.co.uk | **W** allprint.co.uk



All Print Supplies