

RG Reeded Glass Effect Films

¼" and ½" reeded / fluted glass effect PET window film

Product description

50µ reeded / fluted glass effect clear polyester film with a clear solvent based acrylic removable adhesive and 20µ clear polyester release liner. Available in rolls 1520mm wide.

RG6 has a ¼" patterning.

RG12 has a ½" patterning.

Typical uses

Suitable for both indoor use and outdoor for 1 year, vertical exposure in mid-EU climate.

Transforms windows easily and quickly to look like reeded / fluted glass.

Wet application is highly recommended for these products

Shelf life

18 months when stored in original packaging at 21°C and 50% RH.

Physical properties (Average Values)

Film thickness: 50 microns

Adhesive / Thickness: Clear solvent-based acrylic, removable, 15 g

Adhesion to steel: FINAT FTM 1

20 minutes (180°) N/25mm: 8

24 hours (180°) N/25mm: 9

7 days (180°) N/25mm: 10

Product application:

Dimensional stability (mm) 0.000mm

UVA/UVB blk 35%

Application temperature 10°C to 25°C

Service temperature minus 30°C to 60°C

Additional information

Material is warranted for one (1) year from date of shipment. The shelf life of the material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. Only this product is warranted to be free from defects in workmanship or defects. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith. All data values quoted above are typical and should not be used to deem the product defective, if measured values are different.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use.

We reserve the right to make changes to specifications without prior notice.

South Sales: T 01753 696977 | **North Sales:** T 01709 829800

Free Fax 0800 374635 | **E** sales@allprint.co.uk | **W** allprint.co.uk



All Print Supplies