Product Data Sheet March 2024

# DigiPRINT / TSPT15 Gecko Opaque

# Opaque self-adhesive repositionable fabric with grey back

## **Product description**

For printing with Solvent and UV inks.

A self-adhesive fabric with a dark grey coverall reverse.

Repositionable and removable acrylic adhesive on a paper release liner.

\_\_\_\_\_

# Typical uses

Designed for decoration of walls, exhibition stand walls, and general advertising applications.

Suitable for both long term internal and short term external advertising and promotion.

The product is recommended for flat sided applications.

\_\_\_\_\_

#### Shelf life

2 years when stored at 15°C to 25°C and 50% RH.

\_\_\_\_\_

### Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

**Fabric weight (no liner):** 240gsm

Fabric thickness (no liner): 245 microns

**Adhesive data:** 24hr: 2.8N/25mm (FTM1 on glass)

**Tear resistance:** MD: 860N, TD: 880N

Opacity: 99%

**Temperature ranges:** Min. Application Range: plus 10°C

Service Range: minus 10° to plus 50°C

**Flammability**: French standard M1 certified

#### **Application Data**

Ensure product is fully dry and outgassed before use.

Product is suitable for butt joints. Joints should be cut before application to walls. Cuts should always be made with a fresh sharp blade to ensure fabric is cut cleanly. Take care when overlapping the edges as this may result in damage to the printed surface.

Product NOT suitable for wet application. Dry application is essential.

To ensure good bond strength, product must be applied to flat dry, clean, grease free surfaces and not cleaned with products containing silicone.

Product is suitable for smooth surfaces and must be squeegeed well to achieve a good bond.

We recommend surfaces are tested thoroughly before end use.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use. We reserve the right to make changes to specifications without prior notice.

**South Sales:** T 01753 696977 | **North Sales:** T 01709 829800

Free Fax 0800 374635 | E sales@allprint.co.uk | W www.allprint.co.uk

