Product Data Sheet March 2024

# DigiPRINT TSSP225

## 225gsm satin white indoor photo paper

#### **Product description**

For printing with Solvent, Latex and UV inks.

A 225gsm true PE coated paper with a stain finish for use on the current range of eco and true solvent printers. Product also works extremely well with the HP latex printer inks.

The base paper is sourced from certified managed forests.

Typical uses

Suitable for indoor advertising and general poster work.

Due to the high quality of print, material can be used for close up indoor POS applications.

\_\_\_\_\_

**Shelf life** 

2 years when stored at 10°C - 30°C and 30 - 65% RH.

\_\_\_\_\_

#### Physical properties (Average Values)

Tests made at 23°C and 50%RH unless otherwise stated

**Total Weight:** 225 ±7 gsm

**Thickness:** 205 ±5 microns

Whiteness: 150 (CIE)

**Gloss Level (60°):** 17 ±5%

**Opacity:** >90%

### **Application Data**

Product can be used unlaminated for most applications.

If lamination is required to achieve a different finish, it is essential to ensure the print is dry before post print processing.

Prints should be left flat and not rolled or folded for 2 hours to ensure print is dry.

The use of a forced air heater can greatly speed up the drying process.

Profiles are available for the leading printers to help with ink and colour control.

All technical information is based on manufacturer's claims and is believed to be true at time of print but does not constitute a warranty. Due to the complexity of end use the purchaser should carefully consider the fitness and performance of the product for their own application or use. We reserve the right to make changes to specifications without prior notice.

**South Sales:** T 01753 696977 | **North Sales:** T 01709 829800 **Free Fax** 0800 374635 | **E** <u>sales@allprint.co.uk</u> | **W** allprint.co.uk

